

Check Valves		
Disc check valves		
	<p>DISC CHECK VALVE Polyprop.-white 1/4 NPT-Fe ends</p> <ul style="list-style-type: none"> • Disc with seat suitable for O-ring • SS Spring (or Hastelloy option) • O-Ring in Viton (or Kalrez with extra price) • Wide flow section for higher flowrates. • Works in any position, also without spring <p>*Cracking Press: 0,03 Bar *Max Press: 9 Bar *Max Temp: 60 C°</p>	
Code VK2PPFE04N04NV	Sizes: L=51 mm Ex=24 mm	<p>Other Sizes:</p> <p>1 /4 NPT (Ex.24mm L=51mm) 3 /8 NPT (Ex.24mm L=51mm) 1 /2 NPT (Ex.28mm L=63 mm) 3 /4 NPT (Ex.35mm L=63 mm)</p>
SS Ball check Valves		
	<p>BALL CHECK VALVE PVC 1/4 NPT-Fe ends</p> <ul style="list-style-type: none"> • Max Press: 9 Bar • Max Temp: 60 C° • SS Spring + Ball • O-Ring: Buna • Cracking Press. : 0,1 Bar <p>Sizes: Length: 55mm Diam: 25 mm</p>	
	VK4PPBR0202B	<p>PP Check Valve barbed ends:</p> <p>*1/8ID Barbed diam 3x4,4mm *1/4ID Barbed diam 6,3x8,6mm</p> <p>*SS Spring + Ball *Cracking Press.: 0,07 bar *Max Press: 9 Bar</p> <p>Outer Diam: 13 mm (1/8 or 1/4) Length: 35mm (1/8) 52mm (1/4)</p>
Check Valve Teflon Ball + Hastelloy Spring		
	<p>PVDF Check valve Ends: 1/4 NPT male</p> <ul style="list-style-type: none"> • Teflon ball+ Hastelloy spring. • O-Ring Viton • Cracking Press: 0,2 Bar (std) • Hole bore: 5 mm 	
	<p>> Other available sizes:</p> <p>Ends 3/8NPT L= 38mm Ex= 20,5 mm <i>Hole bore 6mm</i> Ends 1/2NPT L= 45mm Ex= 23 mm <i>Hole bore 9mm</i></p>	
	Diaphragm check Valves	
	<p>Polyprop. Diaphr. check. *Zero Cracking Press. Barbed ends for 1/8ID tubing > Barbed Diam: 3mm x 4,4mm < *Viton Diaphragm *Max Press 9 Bar *Outer Diam: 20 mm *L: 33 mm *Body thickness: 7mm</p>	
		<p>PVDF Diaphr. check. *Zero Cracking Press. Barbed ends for 3/16 ID tubing > Barbed Diam: 4,7mm x 6,4mm < *Viton Diaphragm *Max Press 9 Bar *Outer Diam: 20 mm *L: 42 mm *Body thickness: 7mm</p>